

CHARACTER
COLLECTION
— by Somerset™ —



NATURAL KNOTS, MARKINGS AND VARIATIONS IN GRAIN AND COLOR GIVE YOUR SPACE REAL CHARACTER.



S SOLID
3/4" thick, random lengths up to 6-1/2'
WIDTHS: 3-1/4", 4", 5"

S SOLIDPLUS® ENGINEERED
1/2" thick, 3mm thick solid sawn wear layer, 8-ply, random lengths up to 6-1/2'
WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

02/19

CHARACTER: SOLID



Product:	Somerset Character Collection Solid Hardwood Flooring			
Species:	Hickory & White Oak			
Grade:	Proprietary Somerset character grade that will include, but is not limited to, small, sound open knots; mineral; worm holes; heartwood; sapwood; and burls.			
Dimensions:	Thickness: 3/4"* Widths: 3-1/4", 4", 5" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with the National Wood Flooring Association.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	3 1/4" Width	4" Width	5" Width	Species
	Hickory (Natural)	CP314HCB	CP41HCB	CP51HCB Hickory
	White Oak (Natural)	CP314WOB	CP41WOB	CP51WOB White Oak
	Hickory Saddle	CP314HSAB	CP41HSAB	CP51HSAB Hickory
	Hickory Ember	CP314HEB	CP41HEB	CP51HEB Hickory
Gloss Level:	Low Gloss			
Janka Hardness:	Species	Lbs		
	White Oak	1360	Hickory	1820
			<i>Reference (Red Oak)</i>	1290
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			

CHARACTER: **SOLIDPLUS**® ENGINEERED



Product:	Somerset Character Collection Solid Plus Engineered Hardwood Flooring			
Species:	Hickory, Hard Maple, or White Oak			
Grade:	Proprietary Somerset character grade that will include, but is not limited to, small, sound open knots; mineral; worm holes; heartwood; sapwood; and burls.			
Dimensions:	Thickness: 1/2"*; 3mm* thick solid dry sawn wear layer Widths: 3-1/4", 5" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	8-ply cross-grain engineered construction; 7-ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	3/4" Width	5" Width	Wear Layer Species	
	Maple Pine	EP314MPIE	EP51MPIE	Hard Maple
	Hickory (Natural)	EP314CHHCE	EP51CHHCE	Hickory
	Maple Onyx	EP314MOXE	EP51MOXE	Hard Maple
	White Oak (Natural)	EP314WOE	EP51WOE	White Oak
	Hickory Saddle	EP314HSAE	EP51HSAE	Hickory
	Hickory Ember	EP314HEE	EP51HEE	Hickory
Gloss Level:	Low Gloss			
Janka Hardness:	Species	Lbs		
	Hard Maple	1450	Hickory 1820	
	White Oak	1360	Reference (Red Oak) 1290	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Formaldehyde Emissions:	ASTM D6007; BQL (below quantification limit—.008ppm) TSCA Title VI Compliant			
Critical Radiant Flux (CRF):	ASTM E648 (0.33 critical radial flux)			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			