


**HOMESTYLE**  
COLLECTION  
*by Somerset™*



**NATURAL RED OAK**  
Red Oak

**BUTTERSCOTCH**  
White Oak

**GUNSTOCK**  
Red Oak

**NATURAL WHITE OAK**  
White Oak

**PROVINCIAL**  
Red Oak

**METRO BROWN**  
White Oak

**CHARCOAL**  
White Oak

SOLID APPALACHIAN OAK FLOORING  
WITH THE ADDED DESIGN FEATURE  
OF A FOUR-SIDED EASED EDGE.



**S SOLID**  
3/4" thick, random lengths up to 6-1/2'  
WIDTHS: 2-1/4", 3-1/4"



PRODUCT SPECIFICATION SHEET

05/15

# HOMESTYLE: SOLID



Product:	Somerset <b>Homestyle Collection</b> Solid Hardwood Flooring		
Species:	Red Oak or White Oak (Somerset does not mix species.)		
Grade:	Proprietary Somerset grade		
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 2-1/4", 3-1/4" <b>Lengths:</b> Random from 10" up to 6-1/2' *Nominal		
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal ( <a href="http://www.appalachianwood.org">www.appalachianwood.org</a> ). Product is also affiliated with the National Wood Flooring Association.		
Profile:	Eased Edge, Eased End		
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish		
Colors:	<b>2 1/4" Width</b>	<b>3 1/4" Width</b>	<b>Species</b>
	Natural Red Oak	PS2701B	S3701B Red Oak
	Butterscotch	PS2703B	PS3703B White Oak
	Gunstock	PS2714B	PS3714B Red Oak
	Natural White Oak	PS2706B	PS3706B White Oak
	Provincial	PS2707B	PS3707B Red Oak
	Metro Brown	PS2716B	PS3716B White Oak
	Charcoal	PS2740B	PS3740B White Oak
Gloss Level:	Semi Gloss		
Janka Hardness:	<b>Species</b>	<b>Lbs</b>	
	Red Oak	1290	
	White Oak	1360	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request		
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are available at <a href="http://www.somersetfloors.com">www.somersetfloors.com</a>		
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )		
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )		
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer		