



Walnut  
(Walnut)



American Cherry  
(Cherry)



Hickory  
(Hickory)



Maple  
(Maple)



White Oak  
(White Oak)



Hickory Saddle  
(Hickory)



Gunstock  
(White Oak)

GIVE YOUR SPACE SPECIAL CHARACTER WITH  
HARDWOOD FLOORING THAT FEATURES NATURAL KNOTS,  
VARIATIONS, AND MARKINGS.



**S SOLID**

3/4" thick; random lengths

WIDTHS: 3-1/4", 4", 5"

**E ENGINEERED**

1/2" thick, solid sawn face; 8 plies;  
random lengths

WIDTHS: 3-1/4", 5"

# CHARACTER: SOLID



Product:	Somerset <b>Character Collection</b> Solid Hardwood Flooring					
Species:	Walnut, American Cherry, Hickory, Maple, or White Oak					
Grade:	Proprietary Somerset character grade will include but is not limited to, small, sound open knots, mineral, mineral streaks, worm holes, heartwood, sapwood, and burls.					
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 3-1/4", 4", 5" <b>Lengths:</b> Random (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>					
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood.					
Profile:	Eased Edge, Square End					
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish					
Colors:	<b>3 1/4" Width</b>	<b>4" Width</b>	<b>5" Width</b>	<b>Species</b>		
	Walnut (Natural)	CP314WA	CP41WA	CP51WA	Walnut	
	American Cherry (Natural)	CP314AC	CP41AC	CP51AC	American Cherry	
	Hickory (Natural)	CP314HC	CP41HC	CP51HC	Hickory	
	Maple (Natural)	CP314MP	CP41MP	CP51MP	Hard Maple	
	White Oak (Natural)	CP314WO	CP41WO	CP51WO	White Oak	
	Hickory Saddle	CP314HSA	CP41HSA	CP51HSA	Hickory	
	Gunstock	CP314WGS	CP41WGS	CP51WGS	White Oak	
Gloss Level:	Low Gloss					
Janka Hardness:	<b>Species</b>	<b>Lbs</b>				
	Walnut	1010	Am. Cherry	950	Hickory	1820
	White Oak	1360	Maple	1450	Reference (Red Oak)	1290
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request					
Flame Spread:	Class C					
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007)					
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )					
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )					
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer					

# CHARACTER: ENGINEERED



Product:	Somerset <b>Character Collection</b> Engineered Hardwood Flooring			
Species:	Walnut, American Cherry, Hickory, Maple, or White Oak			
Grade:	Proprietary Somerset character grade will include but is not limited to, small, sound open knots, mineral, mineral streaks, worm holes, heartwood, sapwood, and burls.			
Dimensions:	<b>Thickness:</b> 1/2"*; 3mm* dry sawn face <b>Widths:</b> 3-1/4", 5" <b>Lengths:</b> Random Lengths up to 6-1/2' <small>*Nominal</small>			
Construction:	8 ply cross grain laminated construction; 7 ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>3/4" Width</b>	<b>5" Width</b>	<b>Wear Layer Species</b>	
	Walnut (Natural)	EP314WAE	EP51WAE	Walnut
	American Cherry (Natural)	EP314ACE	EP51ACE	American Cherry
	Hickory (Natural)	EP314CHHCE	EP51CHHCE	Hickory
	Maple (Natural)	EP314CHMPE	EP51CHMPE	Hard Maple
	White Oak (Natural)	EP314WEOE	EP51WEOE	White Oak
	Hickory Saddle	EP314HSAE	EP51HSAE	Hickory
	Gunstock	EP314WGSE	EP51WGSE	White Oak
Gloss Level:	Low Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Walnut	1010	Am. Cherry 950	
	White Oak	1360	Maple 1450	
			Hickory 1820	
			Reference (Red Oak) 1290	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007)			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			