



PRODUCT SPECIFICATION SHEET

08/01/11

# COUNTRY COLLECTION: SOLID

Product:	Somerset <b>Country Collection</b> Solid Hardwood Flooring			
Species:	White Oak or Maple			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.			
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 3-1/4", 5"* <b>Lengths:</b> Random (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>			
Construction:	Traditional 3/4" solid construction featuring hand scraped accents and coloring.			
Profile:	Beveled Edge, Beveled End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>3/4" Width</b>	<b>5" Width</b>	<b>Species</b>	
	Natural White Oak	RP314WO	PR51WO	White Oak
	Toast	RP314TO	RP51TO	Maple
	Forest Brown	RP314FB	RP51FB	Maple
	Desert Tan	RP314DT	RP51DT	Maple
	Royal Brown	RP314RB	RP51RB	White Oak
	Buttercup	RP314BU	RP51BU	White Oak
	Merlot	RP314ML	RP51ML	Maple
Gloss Level:	Low Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Maple	950	Walnut 1010	
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007)			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			