



PRODUCT SPECIFICATION SHEET

08/01/11

# VALUE COLLECTION: SOLID

Product:	Somerset <b>Value Collection</b> Solid Hardwood Flooring			
Species:	Red Oak or White Oak			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.			
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 2-1/4", 3-1/4" <b>Lengths:</b> Random (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>			
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers Inc.'s Verified Sustainable Seal ( <a href="http://www.appalachianwood.org">www.appalachianwood.org</a> ) and is available as a FSC Certified Product (Forest Stewardship Council) at an additional cost. Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.			
Profile:	Eased Edge, Square End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>2 1/4" Width</b>	<b>3 1/4" Width</b>	<b>Species</b>	
	Natural White Oak	PS3101	VS3401	White Oak
	Butterscotch	PS3118	VS3418	White Oak
	Honey	PS3107	VS3407	White Oak
	Dark Chocolate	PS3120	VS3420	White Oak
	Gunstock	PS3104	VS3404	Red Oak
	Vintage Brown	PS3117	VS3417	White Oak
	Saddle	PS3119	VS3419	White Oak
Gloss Level:	Semi Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007)			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	25-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			



PRODUCT SPECIFICATION SHEET

08/01/11

# VALUE COLLECTION: ENGINEERED

Product:	Somerset <b>Value Collection</b> Engineered Hardwood Flooring			
Species:	Red Oak or White Oak			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.			
Dimensions:	<b>Thickness:</b> 3/8"*; 2mm* offset sliced face <b>Widths:</b> 3-1/4", 5" <b>Lengths:</b> Random <small>*Nominal</small>			
Construction:	5 ply cross grain laminated construction.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>3/4" Width</b>	<b>5" Width</b>	<b>Wear Layer Species</b>	
	Natural White Oak	EP3101E	EP5101E	White Oak
	Butterscotch	EP3118E	EP5118E	White Oak
	Honey	EP3107E	EP5107E	White Oak
	Dark Chocolate	EP3120E	EP5120E	White Oak
	Gunstock	EP3104E	EP5104E	Red Oak
	Vintage Brown	EP3117E	EP5117E	White Oak
	Saddle	EP3119E	EP5119E	White Oak
Gloss Level:	Semi Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007)			
Maintenance:	Somerset Ultimate™ Wood Flooring Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	25-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			