

**HAND CRAFTED  
COLLECTION**

*— by Somerset —*



HAND APPLIED TEXTURE,  
MODERN RUSTIC LOOK



**SOLIDPLUS® ENGINEERED**  
1/2" thick, 3mm thick wear layer, 8-ply,  
random lengths from 10" to 6-1/2'  
RANDOM WIDTHS: 3-1/4" – 4" – 5"  
WIDTHS: Maple, Hickory 6"; Oak 7"



PRODUCT SPECIFICATION SHEET

05/23

# HAND CRAFTED: SOLID**PLUS**® ENGINEERED



Product:	Somerset <b>Hand Crafted Collection</b> Solid <b>Plus</b> Engineered Hardwood Flooring				
Species:	Hickory, Hard Maple, or White Oak (Somerset does not mix species.)				
Grade:	Proprietary Somerset grade				
Dimensions:	<b>Thickness:</b> 1/2"*; 3mm* thick solid dry sawn wear layer <b>Widths:</b> 3-1/4" - 4" - 5" Random; 6", 7" <b>Lengths:</b> Random from 10" to 6-1/2' *Nominal				
Construction:	8-ply cross-grain engineered construction; 7-ply hardwood core.				
Profile:	Eased Edges, Eased Ends				
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish				
Colors:		<b>3 1/4" - 4" - 5" Widths</b>	<b>6" Width</b>	<b>7" Width</b>	<b>Wear Layer Species</b>
	Ocean Gray	EPHCOGRLE	EPHCOG6E		Maple
	Dark Forest	EPHCDFRLE	EPHCDF6E		Maple
	Winter Wheat	EPHCWWRLE	EPHCWW6E		Hickory
	Antique Bronze	EPHCABRLE	EPHCAB6E		Hickory
	Buttercup	EPHCBURLE		EPHCBU7E	White Oak
	Royal Brown	EPHCRBRLE		EPHCRB7E	White Oak
	Vintage Oak	EPHCVORLE		EPHCVO7E	White Oak
	Rustic Autumn	EPHCRARLE		EPHCRA7E	White Oak
Gloss Level:	Low Gloss				
Janka Hardness:	<b>Species</b>	<b>Lbs</b>			
	White Oak	1360	Hard Maple	1450	
	Hickory	1820			
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request				
Formaldehyde Emissions:	ASTM D6007; BQL (below quantification limit—.008ppm) TSCA Title VI Compliant				
Critical Radiant Flux (CRF):	ASTM E648 (0.33 critical radial flux)				
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at <a href="http://www.somersetfloors.com">www.somersetfloors.com</a>				
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )				
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )				
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer				