

**SPECIALTY
COLLECTION**

—by Somerset™—



| | | | | | | | | | |
|-----------------|-------------------|---------------|----------------|---------------|-----------------|------------------|----------------|---------------|-------------|
| | | | | | | | | | |
| HICKORY NATURAL | HICKORY MOONLIGHT | HICKORY SPICE | HICKORY NUTMEG | MAPLE NATURAL | MAPLE GREYSTONE | MAPLE TUMBLEWEED | MOUNTAIN BROWN | COUNTRY NIGHT | RUSTIC GREY |
| Hickory | Hickory | Hickory | Hickory | Maple | Maple | Maple | Red Oak | Red Oak | Red Oak |

A COLLECTION OF APPALACHIAN SPECIES THAT OFFERS UNIQUE STYLE AND DESIGN OPTIONS



- S SOLID**
3/4" thick, random lengths up to 6-1/2'
WIDTHS: 2-1/4"(maple), 3-1/4", 4", 5"
RANDOM WIDTHS: 2-1/4" – 3-1/4" – 4"
- S SOLIDPLUS® ENGINEERED**
1/2" thick, 3mm thick wear layer, 8-ply,
random lengths up to 6-1/2'
WIDTHS: 3-1/4", 5"
RANDOM WIDTHS: 3-1/4" – 5" – 7"



PRODUCT SPECIFICATION SHEET

05/23

SPECIALTY: SOLID



| | | | | | | |
|-------------------|--|--|---------------------------|-----------------------|-----------------------|----------------|
| Product: | Somerset Specialty Collection Solid Hardwood Flooring | | | | | |
| Species: | Hickory or Red Oak (Somerset does not mix species.) | | | | | |
| Grade: | Proprietary Somerset grade | | | | | |
| Dimensions: | Thickness: 3/4"* Widths: Hickory: 3-1/4", 4", 5" Random Widths: Oak: 2-1/4" – 3-1/4" – 4" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small> | | | | | |
| Construction: | Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with the National Wood Flooring Association. | | | | | |
| Profile: | Eased Edge, Eased End | | | | | |
| Finish: | Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish | | | | | |
| Colors: | | 2 1/4" Width Strip | 3 1/4" Width Strip | 4" Width Plank | 5" Width Plank | Species |
| | Hickory Natural | | PS314HCB | PP41HCB | PP51HCB | Hickory |
| | Hickory Moonlight | | PS314HMLB | PP41HMLB | PP51HMLB | Hickory |
| | Hickory Spice | | PS314HSPB | PP41HSPB | PP51HSPB | Hickory |
| | Hickory Nutmeg | | PS314HNUB | PP41HNUB | PP51HNUB | Hickory |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | 2 1/4" – 3 1/4" – 4" Random Width Plank | | | Species | |
| Mountain Brown | | PPRWMBB | | | Red Oak | |
| Country Night | | PPRWCNB | | | Red Oak | |
| Rustic Grey | | PPRWRGB | | | Red Oak | |
| Gloss Level: | Hickory, Maple: Semi Gloss Oak: Low Gloss | | | | | |
| Janka Hardness: | Species | Lbs | | | | |
| | Hickory | 1820 | Red Oak | 1290 | | |
| MSDS: | Not required for cured finish, MSDS for Wood Dust available on request | | | | | |
| Installation: | Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com | | | | | |
| Maintenance: | Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com) | | | | | |
| Limited Warranty: | 50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com) | | | | | |
| Molding: | Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer | | | | | |

SPECIALTY: **SOLIDPLUS**® ENGINEERED



| | | | | |
|------------------------------|--|--|-----------------|---------------------------|
| Product: | Somerset Specialty Collection Solid PLUS Engineered Hardwood Flooring | | | |
| Species: | Hickory, Hard Maple, or Red Oak (Somerset does not mix species.) | | | |
| Grade: | Proprietary Somerset grade | | | |
| Dimensions: | Thickness: 1/2"*; 3mm* thick solid dry sawn wear layer Widths: 3-1/4", 5" Random Widths: Oak: 3-1/4" – 5" – 7" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small> | | | |
| Construction: | 8-ply cross-grain engineered construction; 7-ply hardwood core. | | | |
| Profile: | Eased Edge, Eased End | | | |
| Finish: | Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish | | | |
| Colors: | | 3/4" Width | 5" Width | Wear Layer Species |
| | Hickory Natural | EP314SPHCE | EP512SPHCE | Hickory |
| | Hickory Moonlight | EP314SPHME | EP512SPHME | Hickory |
| | Hickory Spice | EP314HSPE | EP512HSPE | Hickory |
| | Hickory Nutmeg | EP314HNUE | EP512HNUE | Hickory |
| | Maple Natural | EP314SPMPE | EP512SPMPE | Hard Maple |
| | Maple Greystone | EP314SPMGE | EP512SPMGE | Hard Maple |
| | Maple Tumbleweed | EP314TUME | EP512TUME | Hard Maple |
| | | 3/4" – 5" – 7" Random Width Plank | | Wear Layer Species |
| | Mountain Brown | EPRWMBE | | Red Oak |
| Country Night | EPRWCNE | | Red Oak | |
| Rustic Grey | EPRWRGE | | Red Oak | |
| Gloss Level: | Hickory, Maple: Semi Gloss Oak: Low Gloss | | | |
| Janka Hardness: | Species | Lbs | | |
| | Hickory | 1820 | Red Oak | 1290 |
| | Hard Maple | 1450 | | |
| MSDS: | Not required for cured finish, MSDS for Wood Dust available on request | | | |
| Formaldehyde Emissions: | ASTM D6007; BQL (below quantification limit—.008ppm) CARB Phase 2 Compliant | | | |
| Critical Radiant Flux (CRF): | ASTM E648 (0.33 critical radial flux) | | | |
| Installation: | Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com | | | |
| Maintenance: | Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com) | | | |
| Limited Warranty: | 50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com) | | | |
| Molding: | Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer | | | |