





SOLID APPALACHIAN OAK FLOORING WITH THE ADDED DESIGN FEATURE OF A FOUR-SIDED EASED EDGE.







PRODUCT SPECIFICATION SHEET

05/15

HOMESTYLE: SOLID



Product:	Somerset Homestyle Collection Solid Hardwood Flooring					
Species:	Red Oak or White Oak (Somerset does not mix species.)					
Grade:	Proprietary Somerset grade					
Dimensions:	Thickness: 3/4"* Widths: 2-1/4", 3-1/4" Lengths: Random from 10" up to 6-1/2' *Nominal					
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with the National Wood Flooring Association.					
Profile:	Eased Edge, Eased End					
Finish:	Ultimate™ Urethane Finish—UV Cured Aluminum Oxide, Abrasion Resistant Finish					
Colors:			2¹/₄" Width	31/4" Width	Species	
	Natural Red Oak		PS2701B	S3701B	Red Oak	
	Butterscotch		PS2703B	PS3703B	White Oak	
	Gunstock		PS2714B	PS3714B	Red Oak	
	Natural White Oak		PS2706B	PS3706B	White Oak	
	Provincial		PS2707B	PS3707B	Red Oak	
	Metro Brown		PS2716B	PS3716B	White Oak	
	Charcoal		PS2740B	PS3740B	White Oak	
Gloss Level:	Semi Gloss					
Janka Hardness:	Species	Lbs				
	Red Oak	1290				
	White Oak	1360				
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request					
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2019.) Installation guidelines are available at www.somersetfloors.com					
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)					
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)					
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer					